



GmbH

Your partner for door-, window- and facade engineering

Handheld screwdriver

pistol form with slide forepart GF-SDP 2200

& hose package

2200 1/min



free accessible sliding clutch for torque adjustment

Field of application :

- mere hand device with manual screw feed
- in connection with automatic screw feeding device MF-2 and hose package
- option manual screw feed „I or J“ + automatic screw feed
- option depth disconnection „C“
- option screwer jaw-forepart „B“ to avoid damage on the profile (e.g. caused by opening screwer jaws)

Application :

- for screwing fastening elements into metal (e.g. plate with drilling screw), PVC, wood or similar material if a torque of 4,5 Nm is not exceeded

Structure :

- handheld screwdriver pistol form (Desoutter) SDP 2200
with torque – sliding clutch adjustable from the outside, lever start and slide forepart

Technical data:

- revs/min : 2200 1/min
- torque : 1,0 Nm – 4,5 Nm
- weight : 1,9 kg
- screw bit : PH2 ; 170 mm long (option split bit)
- screws : countersunk-, drilling- and self-tapping screws
 - screw length 15-40 mm
 - screw diameter Ø 3,5 – 4,2 mm
 - head diameter Ø 6,0 – 8,2 mm

Working posture :

type with automatic screw feed: any posture
type with manual feed: vertical (down) to horizontal posture

version with depth adjustment > GF SDP 2200 C < :



GmbH Geräte- und Vorrichtungsbau
Tel.: 035828 / 72255
Fax: 035828 / 70743

Sohländer Str. 2 02894 Reichenbach OL
Internet: <http://www.gevo-gmbh.de>
E-Mail: kontakt@gevo-gmbh.de