



GmbH

Your partner for door-, window- and facade engineering

Handheld screwdriver

rod form with sliding forepart GF - SD 2200

& hose package

2200 1/min



free accessible sliding clutch for torque adjustment

with press-on start

field of application :

- mere hand device with manual screw feed
- in connection with an automatic screw feeding device MF-2 and hose package
- option manual screw feed „I or J“ + automatic screw feed
- option depth disconnection „C“
- option screwer jaw-forepart „B“ to avoid damage on the profile (e.g. caused by opening screwer jaws)

application :

- for screwing fastening elements into metal (e.g. plate with drilling screw), PVC, wood or similar material if a torque of 4,5 Nm is not exceeded

structure :

- handheld screwdriver rod form (Desoutter) SD 2200 with sliding clutch, adjustable torque, press-on start and sliding forepart

technical data:

- revs/min : 2200 1/min
- torque : 1,0 Nm – 4,5 Nm
- weight : 1,9 kg
- bit : PH2 ; 170 mm long (option parted bit)
- screws : countersunk-, drilling- and self-tapping screws
 - screw length 15 - 40 mm
 - screw diameter Ø 3,5 - Ø 4,2 mm
 - head diameter Ø 6,0 - Ø 8,2 mm

working posture :

- type with automatic screw feed: any posture
- type with manual feed: vertical (down) to horizontal posture

type with depth adjustment > GF SD 2200 C < :



GmbH Geräte- und Vorrichtungsbau
tel.: 035828 / 72255
fax: 035828 / 70743

Sohländer Str. 2 02894 Reichenbach OL
internet: <http://www.gevo-gmbh.de>
e-mail: kontakt@gevo-gmbh.de