



GmbH

Your partner for door,- window- and facade engineering

Handheld screwdriver

rod form with slide forepart HF-SC 1600

& hose package

- 93.023 - 1600 1/min



light version with press-on start

- Field of application:**
- mere hand device with manual screw feed
 - in connection with automatic screw feeding device and hose-package
 - option manual feed for automatic screw feed
 - option depth disconnection „C“

Application :

- for screwing into PVC, wood or similar material, if a torque of 2,6 Nm is not exceeded

Structure :

- handheld screwdriver rof form (Desoutter) HF - SC 1600 with sliding clutch, adjustable torque, press-on start and slide forepart

Technical data:	- revs/min :	1600 1/min
	- torque	0,7 Nm - 2,6 Nm
	- weight	1,080 kg
	- screw-bit	PH2 ; 102 mm long
	- screws	countersunk-, drilling- and self-tapping screws
	screw length	15-40 mm
	screw diameter	Ø 3,5 – 4,2 mm
	head diameter	Ø 6,0 – 8,2 mm

Working posture :

type with automatic screw feed: any posture

type with manual feed: vertical (down) to horizontal posture

Option „C“ depth disconnection :



GmbH Geräte- und Vorrichtungsbau
 Tel.: 035828 / 72255
 Fax: 035828 / 70743

Sohländer Str. 2 02894 Reichenbach OL
 Internet: [http ://www.gevo-gmbh.de](http://www.gevo-gmbh.de)
 E-Mail: kontakt@gevo-gmbh.de