



GmbH

Your partner for door,- window, and facade engineering

Handheld screwdriver

rod form with slide forepart HF - SD 2200

& hose package

- 93.023 - 2200 1/min



with press-on start

Field of application :

- mere hand device with manual screw feed
- in connection with automatic screw feeding device MF-2 and hose package
- with option manual feed for automatic screw feed
- with option depth disconnection „C“

Application :

- for screwing into metal (e.g. plate with drilling screw), PVC, wood or similar material if a torque of 4,5 Nm is not exceeded

Structure :

- handheld screwdriver rod form (Desoutter) HF - SD 2200 with sliding clutch and adjustable torque, press-on start and slide forepart

Technical data:

- | | |
|--------------|---|
| - revs/min: | 2200 revs/min |
| - torque: | 1,0 Nm – 4,5 Nm |
| - weight: | 1,100 kg |
| - screw-bit: | PH2 ; 127 mm long |
| - screws | countersunk-, drilling- and self-tapping screws |
| | screw length 15-40 mm |
| | screw diameter Ø 3,5 – 4,2 mm |
| | head diameter Ø 6,0 – 8,2 mm |

Working posture :

type with automatic screw feed: any posture

type with manual feed: vertical (down) to horizontal posture

Option „C“ depth disconnection :

GmbH Geräte- und Vorrichtungsbau
Tel.: 035828 / 72255
Fax: 035828 / 70743

Sohländer Str. 2 02894 Reichenbach OL
Internet: <http://www.gevo-gmbh.de>
E-Mail: kontakt@gevo-gmbh.de